

OGA Phonak Virto™ R Infinio RightFit™

Custom Digital Hearing Aids (36C79125D0007)

PHONAK
life is on

Government Services | Phone 888-561-7555 | Fax 630-836-9770

RightFit ensures your patient's Virto I-R hearing aids are **crafted as small as possible**, with recommended venting and receiver options pre-selected for optimal **fit and performance**.

Step 1 - Customer Information

Payer:

- ☐ ROES (DALC PH5120018626)
- ☐ Other
- ☐ RACHAP (Enclose payment and if paying by cc, RACHAP authorization form)

Ship To:

Address:

City: State: Zip:

PO #:

Contact Name:

Phone Number:

Email Address:

Patient's Last Name:

Patient's 4 Digit SSN:

Age:

Gender:

Step 2 - Virto I-R



Side:

☐ L ☐ R

Performance level:

☐ 90 (063-0526-01)

☒ Phonak Charger Virto I
(075-0075-11)

Colors:

Faceplate

- ☐ 06 Black
- ☐ 14 Tan
- ☐ 22 Cocoa
- ☐ 26 Pink
- ☐ 28 Brown

Shell

- ☐ 06 Black
- ☐ 14 Tan
- ☐ 22 Cocoa
- ☐ 26 Pink
- ☐ 28 Brown
- ☐ R/B Red/Blue
- ☐ 21 Transparent

Step 3 - Choose the RightFit for your patient (audiogram required)

☐ **RightFit: Smallest possible (for discretion and comfort)**

Includes: AOV¹, AOR², Cerustop and removal line

☐ HS* ☐ CA *Recommend selecting HS for modeling flexibility

OR

☐ **RightFit: Full Shell (for dexterity)**

Includes: AOV¹, AOR² and Cerustop

☐ FS

Step 4 - Additional options

Retention options (shell and lock are same color)

☐ Canal lock

☐ Helix lock

☐ Skeleton lock

Step 5 - Accessories and microphones

Accessories	TV Connector (076-3006-0611070)	☐
	Phonak PartnerMic™ (076-4001-P511070)	☐
	Phonak RemoteControl (076-0067-P500070)	☐

Roger™	Roger On™ V3 (056-3032-P50118) Color: Champagne (P5)	☐
--------	---	--------------------------

Step 6 - Audiometric Data and Preprogramming

Audiometric Information

Please include with all preprogramming requests.
Enter 250-4000Hz for AOV Venting

L						
R						
	250	500	1000	2000	3000	4000

Preprogramming Options

- ☐ ☐ Long Term User (CPI_EXL04)
- ☐ ☐ WhistleBlock On (CPI_WHB23)
- ☐ ☐ Disable Push Button (CPI_PBB00)
- ☐ ☐ Add Speech in Loud Noise Program (CPI_STZP0)
- ☐ ☐ Add Speech in 360 Program (CPI_ZMCPO)
- ☐ ☐ Add Acoustic DuoPhone Program (CPI_ADMPO)
- ☐ ☐ Add Manual Calm w/Tinnitus Masker on (CPI_TPMP0)
- ☐ ☐ Change Soft Noise Reduction to Weak (CPI_SNR04)
- ☐ ☐ Disable Sound Recover (CPI_SRB00)
- ☐ ☐ NAL-NL2 Fitting Formula (CPI_FIT04)

If you prefer to build your own Virto R Infinio, please use page 2 instead.

¹ Acoustically Optimized Vent (AOV) ² Acoustically Optimized Receiver (AOR)

Modified: December 15, 2025

OGA Build your own Phonak Virto™ R Infinio Custom Digital Hearing Aids (36C79125D0007)

Government Services | Phone 888-561-7555 | Fax 630-836-9770

To order Virto I-R with RightFit™, please use the RightFit Order Form.

Step 1 - Customer Information

Payer:

- ☐ ROES (DALC PH5120018626)
- ☐ Other
- ☐ RACHAP (Enclose payment and if paying by cc, RACHAP authorization form)

Ship To:

Address:

City: State: Zip:

PO #:

Contact Name:

Phone Number:

Email Address:

Patient's Last Name:

Patient's 4 Digit SSN:

Age:

Gender:

Step 2 - Virto I-R



Side:

☐ L ☐ R

Performance level:

☐ 90 (063-0526-01)

☒ Phonak Charger Virto I
(075-0075-11)

Colors:

Faceplate

- ☐ 06 Black
- ☐ 14 Tan
- ☐ 22 Cocoa
- ☐ 26 Pink
- ☐ 28 Brown

Shell

- ☐ 06 Black
- ☐ 14 Tan
- ☐ 22 Cocoa
- ☐ 26 Pink
- ☐ 28 Brown
- ☐ 28 Brown
- ☐ R/B Red/Blue
- ☐ 21 Transparent

Step 3 - Options

Shell size	Half Shell	☐
	Full Shell	☐
	Canal	☐
Vent size	AOV ¹ (enter audiogram)	☐
	Manually selected (12/20/25/3L/SAV/No vent)	Left: mm Right: mm
Power level	Left: ☐ M ☐ P ☐ SP ☐ UP	
	Right: ☐ M ☐ P ☐ SP ☐ UP	
Removal line (RF)	Transparent (21)	☐
Wax system	Cerustop (CS)	☐
	Ext. Tube + Spring (WE)	☐
Retention options (shell and lock are same color)	Canal lock	☐
	Helix lock	☐
	Skeleton lock	☐

Step 4 - Accessories and microphones

Accessories	TV Connector (076-3006-0611070)	☐
	Phonak PartnerMic™ (076-4001-P511070)	☐
	Phonak RemoteControl (076-0067-P500070)	☐
Roger™	Roger On™ V3 (056-3032-P50118) Color: Champagne (P5)	☐

Step 5 - Audiometric Data and Preprogramming

Audiometric Information

Please include with all preprogramming requests. Enter 250-4000Hz for AOV Venting

L						
	250	500	1000	2000	3000	4000
R						

Preprogramming Options

- ☐ ☐ Long Term User (CPI_EXL04)
- ☐ ☐ WhistleBlock On (CPI_WHB23)
- ☐ ☐ Disable Push Button (CPI_PBB00)
- ☐ ☐ Add Speech in Loud Noise Program (CPI_STZP0)
- ☐ ☐ Add Speech in 360 Program (CPI_ZMCPO)
- ☐ ☐ Add Acoustic DuoPhone Program (CPI_ADMPO)
- ☐ ☐ Add Manual Calm w/Tinnitus Masker on (CPI_TPMPO)
- ☐ ☐ Change Soft Noise Reduction to Weak (CPI_SNR04)
- ☐ ☐ Disable Sound Recover (CPI_SRB00)
- ☐ ☐ NAL-NL2 Fitting Formula (CPI_FIT04)

Special
Instructions

☐ Call me before you make a change

¹ Acoustically Optimized Vent (AOV)